

700 SERIES VALVES

②

BODY/PORT:
10 = LOWER TEE
30 = LOWER CROSS
21 = UPPER TEE/LOWER TEE
43 = UPPER CROSS/LOWER CROSS
23 = UPPER TEE/LOWER CROSS
90 = Y-BODY (2.5, 3 & 4" only)

KETTLE
28 = FLANGED 90° W/O SPUD
29 = FLANGED 90° W/SPUD

②a

Connetion
M = TRICLAMP
W = WELD ENDS

⑦

NNN-NO TOP
2AP-V20 DIGITAL 24 VDC PNP 0 SOL
2QP-V20 ASI 62 NODE (VER 3.0) 30 VDC 0 SOL
2MP-V20 I/O LINK 0 SOL
5A*-V50 DIGITAL 24VDC PNP 0 SOL
5B*-V50 DIGITAL 24VDC PNP 1 SOL
5E*-V50 ASI 31 NODE (ver 2.1) 30VDC, 0 SOL
5F*-V50 ASI 31 NODE (ver 2.1) 30VDC, 1 SOL
5Q*-V50 ASI 62 NODE (ver 3.0) 30VDC, 0 SOL
5R*-V50 ASI 62 NODE (ver 3.0) 30VDC, 1 SOL
5MP-V50 I/O Link 0 SOL M12 4 Pin
5NP-V50 I/O Link 1 SOL M12 4 Pin
7A*-V70 DIGITAL 24VDC PNP 0 SOL
7B*-V70 DIGITAL 24VDC PNP 1 SOL
7E*-V70 ASI 31 NODE (ver 2.1) 30VDC, 0 SOL
7F*-V70 ASI 31 NODE (ver 2.1) 30VDC, 1 SOL
7G*-V70 ASI 31 NODE (ver 2.1) 30VDC, 2 SOL
7Q*-V70 ASI 62 NODE (ver 3.0) 30VDC, 0 SOL
7R*-V70 ASI 62 NODE (ver 3.0) 30VDC, 1 SOL
7S*-V70 ASI 62 NODE (ver 3.0) 30VDC, 2 SOL
7MP-V70 I/O Link 0 SOL M12 4 Pin
7NP-V70 I/O Link 1 SOL M12 4 Pin
7OP-V70 I/O Link 2 SOL M12 4 Pin
BEI-T-TOP BASIC INTRINSICALLY SAFE 10-30VDC, 0 SOL
BFI-T-TOP BASIC INTRINSICALLY SAFE 10-30VDC, 1 SOL
BGI-T-TOP BASIC INTRINSICALLY SAFE 10-30VDC, 2 SOL

LAST LETTER IS: * OPTION BUILD CODE BELOW
N = CABLEGLAND
P = M12 ADDED TO THINKTOP
for CONNECTIVITY

⑥

SURFACE FINISH / OPTIONS
2 = 3A BRIGHT 32Ra ID BRIGHT OD
4 = PL 20 Ra ID BRIGHT OD
6 = PM 15 Ra W/EP ID BRIGHT OD
R = 3A BRIGHT 32Ra ID BRIGHT OD
with Roulon R641 Stem Bushing
H = 3A BRIGHT 32Ra ID BRIGHT OD
with High Pressure Clamp

⑤

SEAT MATERIAL:
U = BUNA (STD)
E = EPDM
Y = FLUOROELASTOMER

①A

STEM:
Omit for ELASTOMER
TR = PTFE REPLACEABLE
TR2 = PTFE REPLACEABLE

①

316L MODELS:
761 - SANITARY/CIP
771S - THROTTLING
762 - KETTLE/TANK OUTLET

③

ACTUATOR TYPE:
10 = NORMALLY OPEN Piston
20 = NORMALLY CLOSED Piston
15 = NORMALLY OPEN DIAPHRAGM
14D = NORMALLY OPEN (positioner) Diaph
14P = NORMALLY OPEN (positioner) Piston
24P = NORMALLY CLOSED (positioner) Piston

③a

ACTUATOR:
Omit For Diaphragm or Positioner Actuators
S = STD STROKE
L = LONG STROKE
HPS = HIGH PRESSURE STD
HPL = HIGH PRESSURE LONG

④

PORT SIZE:
15 = 1.5"
20 = 2"
25 = 2 1/2"
30 = 3"
40 = 4"
771S Option = Size X Taper (Example 25X6)