




1-1/2" NPT Thread



Ground/Safety Loop



- Notes:
- 316 SS, 18-8 Fasteners, Plastics, and Elastomers
 - Weight: 9.5 lbs.
 - Nozzle Sizes: Range from 0.250" to 0.375"
 - Flow Range: 20 to 80 GPM
 - Pressure Range: 50 to 750 PSIG
 - Min. Full Wash Cycle: 8 to 15 minutes.
 - Clearance: Min: 4.0" passageway I.D.

THIS DRAWING IS THE PROPERTY OF GAMAJET CLEANING SYSTEMS, INC. REPRODUCTIONS AND USE OTHER THAN BORROWER'S AGREEMENT IS PROHIBITED. THIS DOCUMENT SHALL NOT BE LENT OR DISPOSED OF DIRECTLY OR INDIRECTLY NOR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IS SPECIFICALLY FURNISHED.

DRAWN	DATE	Rev.	Description
MQL	08/08/06	1	New Drawing
MQL	08/18/06	2	Change Nozzle size range .
MQL	08/11/08	3	Change in STEM DESIGN
MQL	08/12/08	4	Add View for Ground/safety Loop

UNLESS OTHERWISE SPECIFIED * DIMENSIONS ARE IN INCHES * [] DIMENSIONS ARE mm * DEBURR ALL SURFACES * FILLET RAD.: 0.015 * TOLERANCES: .XX ±0.01 .XXX ±0.005 ANGLE ±1°
MATERIAL: 316 STAINLESS STEEL
FINISH (UNLESS OTHERWISE SPECIFIED): 32 Ra
SCALE: Full

GAMAJET CLEANING SYSTEMS, INC.	
604 Jeffers Circle Exton, PA 19341-2524	
TITLE	CUT SHEET
EQUIPMENT	GAMAJET X
DWG. NO.	GAMAJET X CUT SHEET
SHEET	1 OF 1