



# TOTE CLEANER™

The smarter  
alternative  
to manual  
cleaning

## OVERVIEW

The TrueClean® ToteCleaner™ is designed to remove a variety of products, including thick or dried-on residues, from IBC totes and other industrial containers. The recirculation wash uses less detergent and less water — providing a cost-effective alternative to similar systems.

## FEATURES

- Jet and spray cleaning cycles save time and enable hands-free operation
- Compact, mobile system
- Corrosion-resistant components built to hygienic requirements for food, dairy, and beverage plants
- Performs a variety of washes including Rinse, Caustic/Acid, and Sanitizer
- Recirculation of detergent and water
- Simple VFD with adjustable speed controls

## APPLICATIONS

- Processed food, high-acid food, dairy, beverage, brewery, home & personal care, and chemical industries
- Cleaning 275- and 300-gallon totes and other vessels including small tanks
- Removal of thick, oily, or dried-on product residues
- Restoration of totes to factory condition for sale or return
- Safe removal of hazardous product residues with enclosed, sealed system

MADE IN THE USA

 TrueClean®

## SPECIFICATIONS

- 43 X 23 X 48 inches
- Rated: 200-240v, 50-60Hz, 3-phase  
380-480v, 50-60Hz, 3-phase
- Pressure: 44 psig for MultiMidget units  
85 psig for GJ9 units
- Flow: 20 gpm maximum
- Maximum temperature 200°F
- 316L stainless steel pump, valves, and product contact areas
- 304 stainless steel non-product contact areas
- EPDM elastomer material including seals & gaskets

## INCLUDED

- Cart with 3hp or 10hp pump
- Variable frequency drive (VFD)
- Spray assembly device with IBC lid

## OPTIONS

### SPRAY ASSEMBLY

- High impingement jet device for hard-to-clean, dried-on soils:
  - Alfa Laval GJ9 4-Nozzle 0.150 (see Fig. 1)
- Low impingement spray device for easy-to-clean, water-soluble soils:
  - Toftejorg MultiMidget 360, 3/4" NPT (see Fig. 2)



FIG. 1



FIG. 2

### HOSE KIT

- Part Number: TTC-HOSEKIT
- 3-A and FDA-approved Chlorobutyl hoses with 316L stainless steel ends
- 316L 90° elbows
- 7 heavy, two-piece clamps
- 7 EPDM USP Class VI gaskets
- Outlet adapter

### TOTEFILTER™

- Works with ToteCleaner™ and optional Hose Kit to achieve maximum drainability (see Fig. 3)



FIG. 3